

Differential pressure gauge

Model 1130/1131/1132/1133

Max. static pressure 400 bar

Nominal size 50, 63, 80, 100, 115 and 150 mm

Accuracy: 2 %

Features

- Stainless steel case and several wetted parts
- Static pressure up to 400 bar
- Protection IP65
- Smooth pointer motion
- Dry or liquid filled
- Magnetic coupling, solid front not required

Ranges

0 ... 2,5 mbar up to 0 ... 10 bar

Applications

Chemical and petrochemical industry

Machine and apparatus construction

Filters, Hydraulic systems

Water treatment



Technical specification	1130	1131	1132	1133
Dial size [mm]	50, 63, 80, 100, 115 and 150 (depending on the type)			
Construction	Cylindrical case			
Measuring principle	Magnetic coupling, solid front not required			
Actuator	Piston	Rolling diaphragm	Convuluted diaphragm	
Process fluid migration	Minimal	No		
Range [mm H ₂ O]				25 50 125 250 600 1000
[mbar]	250 500	250	75 250	
[bar]	0,250,5 0,75 1 1,6 3,5 4 5 6 7	0,250,50,75 1	0,250,50,75 1	
Max. static pressure [bar]	200 or 400 (stainless steel body)	200	100	35
Overload capability	Maximum static pressure is also maximum pressure allowed on one side	Max. pressure only on the high pressure side.	Max. static pressure is max. pressure allowed on one side	
Pressure type	Differential			
Process connection	G 1/4 B female, 1/4 NPT female, others on request			
Connection location	Lower, back, in-line	Lower, back, in-line		
Material	Body material, spring, screw, magnet and diaphragm (if used)			
Wetted parts	Aluminum, brass ¹⁾ or stainless steel 316 (1.4401)			¹⁾ not for type 1133
Body, pressure chamber, piston	304 (1.4301)			
Spring and screws	Ceramic			
Magnet	PTFE/Buna-N, Viton or EPDM			
O-Ring/Diaphragm (if used)	304 (1.4301), optional 316L (1.4404)			
Case/bayonet ring	Instrument glass, optional acrylic or toughened glass			
Window	Aluminum, black markings on white background			
Dial	Aluminum, black, optional red set hand or maximum pointer			
Pointer				
Accuracy calibrated ascending	2 %			
Permissible				
Ambient temperature	0 ... 80 °C			
Medium temperature	Max. 80 °C			
Storage temperature	0 ... 60 °C			
Effect	Max. 0,3 % / 10 K			
Protection according EN 60 529/IEC 529	IP65			
Filling liquids	Glycerin, Silicon on request, (not for type 1133)			
Mounting	Direct, optional panel or 2" pipe mounting (only for inline connections), others on request			
Weight dry/filled [kg]	From 0,3 up to 1 depending on the construction			
Accessories, options	3 or 5 way remote mounted manifolds, valves			
Contacts (reed switches) optional	One or 2 SPST (rating 10 VA AC or DC, 100 VAC or DC, 0,5 A AC or DC) One or 2 SPDT (rating 3 VA AC or DC, 30 VAC or DC, 0,3 A AC or DC) Ex-proof versions on request			

